

Janice K. Brewer  
Governor

# ARIZONA DEPARTMENT OF ENVIRONMENTAL QUALITY

1110 West Washington Street • Phoenix, Arizona 85007  
(602) 771-2300 • www.azdeq.gov



Benjamin H. Grumbles  
Director

August 31, 2009

Denison Mines (USA) Corp.  
Attn: Harold Roberts  
1050 17<sup>th</sup> St., Suite 950  
Denver, CO 80265

**RE: Canyon Mine Non-Stormwater Impoundment  
3.04 General Aquifer Protection Permit (APP) No. P-100333**

Inventory Number:	100333	LTF ID:	49736
USAS Number:	030032-04	Place ID:	827

Dear Mr. Roberts:

Enclosed is a signed copy of the Discharge Authorization for the 3.04 General Aquifer Protection Permit (APP) for the above referenced facility. This authorization to discharge was developed pursuant to A.A.C. Title 18, Chapter 11, Article 4, Aquifer Water Quality Standards, and A.A.C. Title 18, Chapter 9, Article 3, Aquifer Protection Permit (APP) rules. If you have any questions regarding this permit or the facility, please feel free to contact Richard Mendolia at 771-4374.

Sincerely,

Michele Robertson, R.G.  
Groundwater Section Manager  
Water Quality Division

Enclosures (2)

cc: Carrollette Winstead, Manager, APP & Drywell Unit, GWS, WQD, ADEQ (w/encl.)  
Matthew Hodge, Manager, WQCDU, WQCS, WQD, ADEQ (w/encl.)  
Cynthia Campbell, Section Manager, WQCS, WQD, ADEQ (w/encl.)  
Robert Olberding, NRO Field Services Unit  
Lynne Dekarske, EPS/Billing, GWS, WQD, ADEQ (w/encl.)

IDU09:0258

Northern Regional Office  
1801 W. Route 66 • Suite 117 • Flagstaff, AZ 86001  
(928) 779-0313


Southern Regional Office  
400 West Congress Street • Suite 433 • Tucson, AZ 85701  
(520) 628-6733



ARIZONA DEPARTMENT OF ENVIRONMENTAL QUALITY

DISCHARGE AUTHORIZATION  
TYPE 3.04 GENERAL AQUIFER PROTECTION PERMIT

Inventory No. 100333  
LTF No.: 49736  
USAS No. 030032-04

Permittee Information:			
Name:	Denison Mines (USA) Corp.		
Address:	1050 17 <sup>th</sup> St. Suite 950 Denver, CO 80265		
Permitted Facility Information(if different from above):			
Name:	Canyon Mine Non-Stormwater Impoundment		
Address:	Tusayan, AZ		
Latitude:	35°52' 58.8" North	Longitude:	112°05'45.6" West
Determination is based on the Notice of Intent (NOI) dated 3/12/09 and technical specifications received 3/20/09.			
<b>Discharge Authorization.</b> Your submittal satisfies the requirements in Arizona Administrative Code (A.A.C.) R18-9-A301(A)(3) and R18-9-A301(B). This Discharge Authorization is No. <b>P-100333</b> . Effective on the date of signature, the permittee is authorized to discharge from the facility at the location specified in the NOI under the terms of A.A.C. R18-9-D304. The permittee shall comply with all design, installation, operation, monitoring, recordkeeping, reporting and closure requirements specified in this general permit and the attachments to this discharge authorization. The permittee shall also comply with all other applicable requirements of 49 A.R.S. 2, and 18 A.A.C. 9, including the General Provisions of Article 3. This Authorization is effective on the date of signature and expires <b>FIVE (5) YEARS</b> from that date. If you wish to renew this Discharge Authorization and no changes have been made to the discharging facility, an NOI must be submitted no later than 30 days before <u>August 31, 2014</u> otherwise, the authorization to discharge will expire (see R18-9-A303(B) and (C)).			
This authorization can be revoked and an individual permit required in the event the permittee fails to comply with the terms of the general permit described in the rules or if the discharge activity causes or contributes to the violation of an Aquifer Water Quality Standard at the applicable point of compliance.			
 Michele Robertson, Manager Groundwater Section Water Quality Division		<u>August 31, 2009</u> Date	

cc: Lynne Dekarske, EPS, GWS

In addition to the requirements of the 3.04 General Permit in A.A.C. R18-9-D304, the permittee has agreed to the following voluntary conditions:

**1. Mine Water Control**

- i. The mine workings, working shaft sumps, and final shaft and vent sumps shall be continuously dewatered to allow the minimum practicable water accumulation.
- ii. The permittee shall conduct a Klinkenberg permeability test on rock samples taken from the bottom of the final shaft and the vent sumps and survey the sumps to identify any features (i.e., fractures, joints, faults, or bedding planes) which may convey fluids out of sumps, prior to use. If permeability tests indicate that the permeability of the rock mass is greater than  $1.0 \times 10^{-7}$  cm/sec the permittee shall provide notice to ADEQ Groundwater Section and initiate within 30 days, line the sumps with bentonite clay or seal any identified feature that may convey fluids out of the sumps.

**2. Mine Shaft Sump Monitoring**

- i. Denison agrees to measure the daily volume of water pumped from the underground mining areas, and conduct periodic sampling of water pumped from the underground mining areas as follows:

Denison will sample water pumped from the underground mining areas at the point the water discharges to the non-stormwater impoundment on a quarterly basis for the parameters set forth in Table 1 below. If there is no water pumped during a particular quarter, then no sample will be required. Denison will report to ADEQ the results of the daily volume of water pumped and quarterly sampling within 30 days of the end of each of the first two quarters of operation, and on an annual basis thereafter.

- ii. If the sampling results suggest that aquifer water quality standards could be exceeded in groundwater beneath the mine given the depth to groundwater at the mine, Denison will increase the frequency of pumping to mitigate any risk to groundwater.

**3. Financial Capability**

The permittee has demonstrated financial capability under A.R.S. § 49-243(N) and A.A.C. R18-9-A203. The permittee shall maintain financial capability throughout the life of the facility. The estimated closure and post-closure cost is \$30,000 and was demonstrated pursuant to A.A.C. R18-9-A203(C)(2). The closure and post-closure costs shall be evaluated and financial capability updated, if necessary, with each 5-year renewal.

**TABLE 1**  
**DISCHARGE MONITORING/MINE SHAFT SUMP MONITORING**

pH (S.U.)	Total Dissolved Solids (mg/L)	Alkalinity – Total (mg/L)	Specific Conductance (umhos/cm)	Sulfate (mg/L)
Fluoride (mg/L)	Calcium (mg/L)	Magnesium <sup>1</sup> (mg/L)	Potassium <sup>1</sup> (mg/L)	Sodium <sup>1</sup> (mg/L)
Iron <sup>1</sup> (mg/L)	Antimony <sup>1</sup> (mg/L)	Arsenic <sup>1</sup> (mg/L)	Barium <sup>1</sup> (mg/L)	Beryllium <sup>1</sup> (mg/L)
Cadmium <sup>1</sup> (mg/L)	Chromium <sup>1</sup> (mg/L)	Copper <sup>1</sup> (mg/L)	Lead <sup>1</sup> (mg/L)	Manganese <sup>1</sup> (mg/L)
Mercury <sup>1</sup> (mg/L)	Nickel <sup>1</sup> (mg/L)	Selenium <sup>1</sup> (mg/L)	Thallium <sup>1</sup> (mg/L)	Zinc <sup>1</sup> (mg/L)
Gross Alpha Particle Activity (pCi/L)	Vanadium <sup>1</sup> (mg/L)	Radium 228 (pCi/L)	Uranium-Isotopes (pCi/L)	Uranium (mg/L)
	Radium 226 (pCi/L)			

<sup>1</sup> Metals shall be analyzed as total recoverable metals.